

Index

A

- Absolute/dynamic viscosity, 8–9
- Absorbed glass mat (AGM) battery, 20
- Absorption, 9
- ABS truck hydraulic control unit, 8
- ABS truck malfunction system, 8
- Accelerate, 10
- Acceleration, 10–11
- Acceleration test, 11
- Accelerator pedal position (APP) sensor, 47–48
- Accelerator pedals, 17
- Accelerator pump, 11
- Accelerometer, 11–12
- Accident measuring triangle, 1–2
- Accident reconstruction, 12
- AC coupling, 9
- Accumulator, 12
- AC induction motor, 9–10
- Ackermann principle, 12
- Ackermann steering system, 12–13
- AC motor, 525
- Acrylic paint, 13
- Active restraint system, 14
- Active Safety Control Module, 187
- Active sensor, 14
- Active wheel speed sensor (WSS), 615
- Actuator, 14
- Adaptive cruise controller (ACC), 15
- Adaptive learning, 16
- Adaptive memory, 16
- Adaptive testing, 16
- AD converter circuit, 14
- Additive, 17
- Address, 17
- Adhesion, 17
- Adhesive, 17
- Adiabatic process, 17
- Adjustable brake, 17
- Advanced diesel engine management system (ADEMS), 16–17
- Advanced driving assistance systems (ADAS), 398
- Aerobic sealant, 18
- Aerodynamic drag, 18
- Aerodynamics, 18
- A-frame control arm, 19
- Afterburner, 20
- Aftercooler, 20
- After top dead center (ATDC), 52
- Air ABS, 20–21
- Air ABS blink codes, 21
- Air ABS brake modulator, 22
- Air ABS electronic control unit (ECU), 22
- Air bag, 14, 22–23, 134
- Air brake compressor, 23–24
- Air brake double check valve, 24
- Air brake dual air pressure gauge, 24–25
- Air brake pressure protection valve, 25–26
- Air brake reservoir drain valves, 26–27
- Air brake reservoir safety valves, 27–28
- Air brakes, 28, 396–397, 454–455, 462, 490, 506–507, 563–564
- Air cleaner, 29
- Air conditioning, 29–30
- Air-cooled engine, 31
- Air core gauge, 31
- Air dam, 31–32
- Air density, 33
- Air disc brakes, 33–34
- Air flow, 34
- Air flow meter, 34
- Air flow types, 35
- Air-fuel charge, 35
- Air-fuel ratio, 35
- Air-fuel ratio sensor, 35
- Air gap, 35
- Air injection reactor (AIR), 22
- Air-over-hydraulic brake system, 36
- Air spring suspension, 36
- Air standard dual cycle, 37
- Air-to-fuel ratio (AFR), 19

- Air turbulence, 37
- Align, 37
- ALLDATA, 37
- All-electric drive mode, 37
- Alloy, 38
- All-wheel drive (AWD) shift motor, 7
- All-wheel drive (AWD) vehicle, 7, 58, 169–170
- Alphanumeric code, 38
- Alternating current (AC), 9
- Alternative fuels, 38
- Alternator, 38–39
- Aluminum bearing material, 39
- Ambient air temperature, 39
- Amboide gearset, 39–40
- American Petroleum Institute (API) oil service classification, 46
- American Society of Mechanical Engineers (ASME), 50
- American Trucking Associations (ATA) connector, 51
- American Wire Gauge (AWG) system, 58
- Ammeter, 41
- Ammeter shunt, 41–42
- Amperage, 42
- Ampere-hour, 42
- Amperes, 42
- Ampere's rule, 42
- Ampere-turn, 42
- Amplifier piston, 42
- Amplitude, 41
- Anaerobic sealant, 42
- Analog, 43
- Analog multimeter, 43
- Analog signal, 43, 178
- Analog-to-digital (AD) converter, 14
- Anemometer, 43
- Aneroid, 43
- Annealing, 44
- Annulus, 44
- Anode, 44
- Antechamber, 419
- Anti-dive, 44
- Antifreeze, 44
- Anti-lock brake system (ABS), 7–8
- Antioxidants, 44
- Anti-rattle clips, 45
- Anti-roll bar. *See* Stabilizer bar
- Anti-squat, 45, 313
- Anti-sway bar. *See* Stabilizer bar
- Apex, 46, 78
- API donut, 46
- A-pillar, 45–46
- API service classification, 46
- API starburst, 47
- A-post. *See* A-pillar
- Application valve, 48
- Aramid, 48
- Armature, 48–49
- Articulated, 49
- Articulated bus, 49
- Articulation test, 49
- Asbestosis, 49
- Ash content, 49–50
- Aspect ratio, 50
- Assembly line communications link (ALCL), 37
- Assembly line diagnostic link (ALDL), 37, 183
- Assist hybrid, 50
- Asymmetrical, 50
- Atmospheric pressure, 53
- Atom, 53
- Atomization, 53
- Atomize, 53
- Automated driving systems (ADS), 18
- Automated safety transmission (AST), 55
- Automatic four wheel drive (AUTO-4WD), 53
- Automatic locking differential, 53
- Automatic locking hubs, 53–54
- Automatic shutdown (ASD), 49
- Automatic transaxle, 54
- Automatic transfer case (ATC), 51–52, 53
- Automatic transfer case control module (ATCM), 52
- Automatic transmission, 54–55
- Automatic transmission fluid (ATF), 52, 54–55
- Automobile Manufacturers Association (AMA), 599
- Automotive, 12
- Automotive A/C servicing, 56
- Automotive brake system, 103, 358–359, 422
- Automotive Service Excellence (ASE), 49
- Automotive suspension, 508–509
- Autonomous vehicle (AV), 56, 57
- Autonomous vehicle levels, 56
- Auto ranging, 53
- AutoShift and AutoShift generation II manual automatic transmissions, 56–57
- AutoShift truck transmissions, 57
- Available voltage in a circuit, 57–58
- Axial, 59
- Axial load, 59
- Axial motion, 59
- Axial play, 59
- Axis, 59
- Axis system, 59–60
- Axle, 60
- Axle bearing, 60
- Axle windup, 60–61
- Axle yaw, 61

B

- B20, 65
- Babbitt, 65
- Backfire, 65–66
- Backing plate, 66
- Backlash, 66
- Backlight, 66
- Backpressure, 67
- Backside spacing, 67
- Back spacing, 65
- Back taper, 65
- Backup camera, 67
- Bakelite, 67
- Balance shaft, 67
- Ball bearing, 67
- Ball joint, 68
- Banjo axle, 68–69
- Bar, 69
- Barometric manifold
 - absolute pressure (BMAP) sensor, 69
- Barometric pressure, 69
- Barometric pressure (BARO) sensor, 69
- Base, 70
- Base circle, 70
- Base timing, 70
- Basic mathematics
 - (addition, subtraction, multiplication, and division), 71
- Battery, 71
- Battery case, 71
- Battery charging, 71
- Battery conductance
 - testing, 72–73
- Battery conductance test
 - procedure, 72
- Battery discharging, 73
- Battery equalizer, 74
- Battery isolator systems, 74
- Battery pack SOC, 75
- Battery pack visual
 - signal, 75
- Battery state-of-charge (SOC), 75
- Battery state-of-charge
 - indicator, 75
- Battery terminals, 75–76
- Baud rate, 76
- Bayonet Neil-Concelman (BNC) connector, 92
- Bead, 77
- Bead base, 78
- Bead bundle, 78
- Bead coils, 78
- Bead cord, 78
- Bead face, 78
- Bead filler, 78
- Bead heel, 78
- Bead seat, 78
- Bead toe, 78
- Bearing, 78
- Bearing (inside diameter), 79
- Bearing cap, 79
- Bearing cone, 79
- Bearing crush, 80
- Bearingized, 80
- Bearing lubrication, 80
- Beating vibration, 80–81
- Before top dead center (BTDC), 81
- Belleville spring, 81
- Bell housing, 81
- Belt, 81
- Belt alternator starter (BAS), 82
- Belt-driven starter
 - generator (BSG), 513
- Belt system, 81–82
- Belt tension, 83
- Belt tensioner, 83
- Bendix drive, 84
- Bevel gears, 84–85
- Bias-belted tire, 86
- Biasing, 87
- Bias-ply tire, 87
- Bias voltage, 87
- Bidirectional
 - communication, 87
- Big end, 87
- Bimetal gauge, 87
- Bimetallic, 87
- Binary, 87
- Biodiesel, 88
- Bipolar, 88
- Bit, 88
- Black smoke, 88
- Blink/flash codes, 88–89
- Blockchain framework, 89
- Block diagram, 89
- Blocker rings, 90
- Block learn function, 89
- Blowby gases, 90
- Blower, 468
- Blower motor, 90
- Blow-off valve (BOV), 90
- Blue smoke, 91
- Bluetooth, 91–92
- Bluetooth detection, 91–92
- Bobtail proportioning
 - valve, 92–93
- Body control area network (B-CAN), 76
- Body control module (BCM), 76, 366, 444–445
- Body ground wire, 93
- Bogie axle, 93
- Boiling point, 93
- Bolt, 93
- Bolt circle, 93
- Bolt pattern, 93
- Boom vibration, 94
- Boost, 94
- Boost control, 94
- Bore, 94
- Borescope, 94–95
- Bosch peak-and-hold
 - injector waveform, 95
- Bottom dead center (BDC), 3–4, 77, 198, 522
- Bottom end, 95
- Bound electrons, 95
- Bowden cable, 95
- Bowed (buckled) frame, 95
- Boxer ICE, 95
- Boyle's Law, 95–96
- Brake assist (BA/BAS), 97, 204–205
- Brake bleeding, 96–97
- Brake booster, 97
- Brake caliper, 109–110. *See also* Caliper
- Brake chamber, 97–98
- Brake fade, 98–99
- Brake fluid, 99–100
- Brake horsepower (BHP), 85–86

- Brake lines, 100
- Brake mean effective
 - pressure (BMEP), 92
- Brake pad, 100
- Brake pressure modulator
 - valve (BPMV), 211
- Brake rotor, 101
- Brakes, 522
- Brake specific fuel
 - consumption
 - (BSFC), 101–102, 104
- Braking performance, 102
- Braking ratio, 102
- Braking stability, 102
- Braking system, 103
- Breaker points, 104
- Breakout box, 104
- Brinelling, 104
- British Thermal Unit
 - (BTU), 104
- Brushes, 104
- Buffer, 104
- Bulkhead, 104, 240
- Bump steer, 104
- Bus, 105
- Bus configuration, 105
- Bushing, 105
- Buss bar, 105
- Butterfly valve. *See* Throttle
- Butt splice, 105
- Bypass hose, 105–106
- Bypass valve. *See* Blow-off
 - valve (BOV)
- Byte, 106
- C**
- Cab forward, 138
- Cab-over-engine
 - (COE), 138
- Cage, 109, 465
- Calibration gas, 109
- Caliper, 109–110
- Calories, 110
- Calorific value (fuel), 110
- Camber, 111
- Cam follower. *See* Lifter;
 - Valve lifter
- Camshaft, 111
- Camshaft gear backlash, 111
- Camshaft gear runout, 112
- Camshaft lobe, 112
- Camshaft position (CMP)
 - sensor, 112
- Cantilever axle, 116
- Capacitance, 116
- Capacitor, 116
- Capacitor capsule MAP
 - sensor, 116
- Capacitor discharge
 - ignition (CDI)
 - system, 123
- Carbon, 116
- Carbon-core wire, 116–117
- Carbon dioxide (CO₂), 117
- Carbon monoxide (CO),
 - 117, 138
- Carbon residue, 117
- Carburetor, 117–118, 218
- Carburizing, 118
- Carcass, 118
- Carcass plies, 119
- Case-hardening, 119
- Case/model-based
 - diagnostic
 - reasoning, 119
- Caster, 119–120
- Caster sweep, 120
- Catalyst, 120–121
- Catalytic converter, 121
- Catalytic substrate, 121
- Cat-back exhaust
 - system, 121
- Catch tank, 121
- Cathode, 121
- Cathode ray tube (CRT), 121
- Cavitation erosion, 122
- Cell, 124
- Center bearing, 124–125
- Center bolt, 125
- Centerline steering, 126
- Centerlink, 126
- Center of gravity (CG),
 - 125–126, 459
- Central processing unit
 - (CPU), 126, 152
- Centrifugal advance, 126
- Centrifugal force, 126, 127
- Centrifugal oil filter, 126
- Centrifugal
 - supercharger, 127
- Centripetal force, 127
- Cetane, 127
- Cetane improvers, 128
- Chain and sprocket
 - drive, 128
- Chain tensioner, 128
- Chamfered edge, 129
- Chamfered strut, 129
- Charge air cooler
 - (CAC), 109
- Charles's Law, 129
- Chassis, 129
- Chassis dynamometer,
 - 199–200
- Chassis ground, 129
- Check engine light, 129
- Check valve, 129
- Chlorofluorocarbon, 129
- Choke, 130
- Circuit, 130
- Circuit breaker, 131
- Circuit number, 131
- Circuit resistance tests, 131
- Circuit sensing, 131
- Circular mil, 131
- Circumference, 131
- Class B Data
 - Communications
 - Network Interface,
 - 132–133
- Class 2 serial
 - communications, 132
- Clearance volume, 133
- C-lock axle, 133
- Clock generator, 133
- Clock spring, 134
- Closed loop, 134
- Closing ramp, 134
- Cloud point, 134
- Clutch, 134–135
- Clutch brake, 135–136
- Clutch disc, 137
- Cocktail shaker
 - piston, 138
- Coefficient of friction,
 - 138–139
- Cogged belt, 139
- Coil-on-plug (COP) ignition
 - system, 151
- Coil spring, 139
- Coke, 139

- Cold cranking amps (CCA), 122
- Collector, 139
- Collision alert indicators, 139–140
- Combination valve, 140
- Combustion, 3, 5–6, 140
- Combustion chamber, 140
- Comet 5 piston, 141
- Common rail fuel injection, 141–142
- Companion cylinder, 142
- Companion flange, 142–143
- Compensating port, 143
- Component alignment, 37
- Compound-wound motor, 144
- Comprehensive component monitor (CCM), 123, 144
- Compressed natural gas (CNG), 138
- Compressibility, 144
- Compression brake, 144
- Compression ignition engine, 4–6. *See also* Diesel engine
- Compression ratio, 3, 5, 144–145
- Compression sensing ignition, 145
- Computer command control (C3), 122
- Condensation point, 145
- Condenses, 145
- Conditional Driving Automation, 145–146
- Conduction, 146
- Conductive materials, 146
- Conductivity, 72–73
- Conductor, 146
- Cone clutch, 147
- Connected vehicle, 147
- Connecting rod, 147
- Connector, 147
- Constant velocity (CV) joint, 158–159
- Contamination, 147
- Continuity tester, 147
- Continuously variable transmission (CVT), 159–160
- Continuous monitor, 148
- Continuous port fuel injection (CPI), 152
- Control arm, 148
- Control device, 148
- Controller area network (CAN), 76, 113–116, 139, 149, 206, 474
- Control module, 149
- Convection, 149
- Conventional current theory, 149
- Converter enhanced electronically managed automated transmission (CEEMAT), 124
- Coolant, 150
- Coolant reservoir tank, 150
- Cooling fan, 150
- Cooling system, 150–151
- Cooperative fuel research (CFR) engine, 128
- Core-out plug, 152
- Corporate Average Fuel Economy (CAFE), 109
- Corrosion, 152
- Corrosion inhibitors, 152
- Corrosion test, 152
- Corrosive, 152
- Co-solvent, 152
- Cotter pin, 152
- Counterelectromotive force (CEMF), 124, 485
- Cracking, 153
- Crank arm/throw, 154–155
- Crankcase, 153
- Crankcase depression regulator (CDR), 123–124
- Crankcase ventilation, 153
- Cranking amperes (CA), 109
- Cranking circuit, 153
- Cranking motor. *See* Starter motor
- Crankshaft, 153–154
- Crankshaft position (CKP) sensor, 131–132
- Crank web, 154–155
- Crash data retrieval (CDR), 12
- Crate engine, 155
- Cross camber, 155
- Cross caster, 155–156
- Crossfire, 156
- Crossflow cylinder head, 156
- Cross weight, 156
- Cruise control, 156
- Cruise control resume/increase switch, 156–157
- Cruise control set/decrease switch, 157
- Cruise control switch, 157–158
- Curb weight, 158
- Current, 158
- Current limiting hump, 158
- Customary measuring system, 158
- Cycle, 160
- Cylinder block, 160
- Cylinder deck, 161
- Cylinder head, 161
- Cylinder head temperature (CHT) sensor, 130
- Cylinder hone, 161
- Cylinder liner, 161
- D**
- Dampening, 163
- Damper. *See* Harmonic balancer
- Damping, 163–164
- Data, 164
- Data bus communication, 164–165
- Data link connector (DLC), 37, 183
- Data stream, 165
- Datum plane, 165
- DC generator, 165
- Dead axle, 166
- Decimal, 165
- Decompressor, 165–166

- Dedicated short-range communications (DSRC), 197
- De Dion rear axle, 166
- Deep-cycle battery, 166
- Deflection rate, 167
- Defogger, 167
- Defroster, 167
- Deglazing, 167
- Delphi design, 75
- Delta-wound stator, 167–168
- Department of Transportation (DOT) tire certification codes, 185–186
- Depth, 168
- Detergent additives, 168
- Detonation, 168
- DEX-COOL, 168, 379
- Diagnostic chart, 169
- Diagnostic executive, 169
- Diagnostic trouble codes (DTCs), 197, 366, 405–406
- Diagonal braking system, 169–170
- Dial bore gauge, 170
- Dial indicator, 170–171
- Diameter, 171
- Diamond-shaped frame, 171
- Diaphragm, 172
- Diaphragm spring, 172
- Die grinder, 172
- Dielectric, 172
- Dielectric grease, 172
- Dielectric strength, 172
- Diesel engine, 172–173
- Diesel exhaust fluid (DEF), 166–167, 481
- Diesel fuel, 173–174
- Diesel fuel #1, 175
- Diesel fuel #2, 175
- Diesel fuel heater, 174–175
- Diesel fuel injector, 473
- Diesel knock, 175
- Diesel oxidation catalyst (DOC), 120–121, 183–184
- Diesel particulate filter (DPF), 120, 176, 188
- Diesel plunger pump, 176
- Differential, 177
- Digital-analog converter (DAC), 14
- Digital multimeter (DMM), 187, 389
- Digital radio, 177
- Digital signal, 178
- Digital storage oscilloscope (DSO), 196–197, 388
- Digital thermometer, 178
- Dilution differential ratio, 178
- Diode, 178
- Diode trio, 178
- Dip stick, 178
- Direct current (DC), 9, 165
- Direct/distributorless ignition system (DIS), 168
- Direct drive, 179
- Direct ignition (DI), 168–169
- Direct Injection (DI), 5, 169
- Directional tires, 179
- Directional wheels, 179–180
- Disc brakes, 180–181
- Discrete device, 181
- Dispersants, 181
- Displacement, 181–182
- Distributor, 182
- Distributor ignition (DI), 169
- Distributor indexing, 182
- Distributorless ignition system (DIS). *See* Waste-spark ignition
- Distributor-type diesel injection pump, 182–183
- Division, 183
- Dog clutch, 184
- Dog tracking, 184
- Dolly, 184
- Doppler effect, 184–185
- Doppler radar, 436
- Double-cardan joint, 581–582
- Double-wishbone modified strut suspension, 186–187
- Downdraft carburetor, 187
- Drag, 188
- Drag coefficient, 189
- Drag link, 189
- Drift, 189
- Drivability, 190
- Driveline, 190. *See also* Drivetrain
- Driveline angle phasing, 190
- Driver information center (DIC), 172
- Driver monitoring system (DMS), 187
- Driveshaft, 191, 425–426
- Driveshaft angles measurement, 191–192
- Driveshaft balancing, 192–193
- Drivetrain, 193
- Driving automation, 193–194
- Dropping point, 194
- Drum brakes, 194–195
- Drum brakes duo-servo incremental self-adjuster, 195
- Drum brakes leading-trailing incremental self-adjuster, 195–196
- Dry liner, 344
- Dry manifold, 196
- Dry park test, 196
- Dry sump lubrication system, 196
- Dry weight, 196
- Dual-mass flywheel, 198
- Dual master cylinder, 198
- Dual motor-generator hybrid, 198
- Dual overhead camsha_ (DOHC), 389
- Dump valve, 90
- Duration, 198–199
- Durometer, 199

Duty cycle, 199
 Dwell, 199
 Dwell section, 199
 Dynamometer (Dyno),
 199–200

E

E-85, 203
 Earthmoving machines, 203
 Eccentric, 205
 E-coil, 205
 Elastomer, 208
 Electric A/C
 compressor, 208
 Electrical burn, 210
 Electrical fire, 210
 Electrical ground, 275
 Electrically assisted steering
 (EAS), 203–204
 Electrically powered
 hydraulic steering
 (EPHS), 219–220
 Electrical solvent, 210
 Electric brake retarder, 208
 Electric circuit, 208
 Electric device, 208
 Electricity, 210
 Electric motor, 208–209
 Electric parking brake
 (EPB), 210
 Electric power steering
 (EPS), 203–204
 Electric shock, 210
 Electric vehicles (EVs), 20,
 21, 37, 223–224
 Electric water pump, 210
 Electrodes, 211
 Electro-hydraulic brake
 assist systems, 211
 Electrolyte, 211
 Electromagnet, 211
 Electromagnetic clutch, 211
 Electromagnetic field
 (EMF), 211–212
 Electromagnetic induction,
 212, 213
 Electromagnetic interference
 (EMI), 218
 Electromagnetics, 213
 Electromagnetic
 solenoid, 212
 Electromagnetism, 213
 Electromotive force (EMF),
 217, 370, 413,
 414, 485
 Electron, 214
 Electron flow theory, 214
 Electronically erasable
 programmable
 read only memory
 (EEPROM), 207
 Electronic brake control
 module (EBCM),
 139–140, 205, 211
 Electronic braking system
 (EBS), 21
 Electronic control unit
 (ECU), 22, 207
 Electronic Data Systems
 (EDS), 386
 Electronic device, 214
 Electronic distributor unit
 (EDU) injector,
 222–223
 Electronic fuel injection
 (EFI), 207
 Electronic fuel injectors,
 214–216
 Electronic ignition, 216
 Electronic ignition
 module, 216
 Electronic listening
 device, 217
 Electronic returnless fuel
 system (ERFS), 220
 Electronic service
 information
 (ESI), 221
 Electronic service tools
 (EST), 221, 479
 Electronic spark control
 (ESC), 220
 Electronic spark timing
 (EST), 222
 Electronic unit injector
 (EUI), 16, 222–223
 Electronic vibration
 analyzer (EVA), 224
 Electrostatic discharge
 (ESD), 220
 Electrostatic field, 217
 Element, 217
 Embittered ethylene
 glycol, 217
 Emergency brake assist
 (EBA), 204–205
 Emergency flasher
 system, 217
 Emission gases, 218
 Emulsion, 218
 Emulsion tube, 218
 Enable criteria, 218
 Endplay, 218
 Energy, 218
 Energy-absorbing steering
 column operation,
 218–219
 Engine control module
 (ECM), 16–17, 88,
 89, 533
 Engine control unit (ECU),
 89, 303–304
 Engine coolant temperature
 (ECT) sensor, 206
 Engine/electronic control
 module (ECM),
 205–206
 Engine fuel temperature
 (EFT) sensor, 207
 Engine management
 computer (EMC), 310
 Engine Manufacturer
 Diagnostic
 (EMD), 217
 Engine mapping, 219
 Engine speed sensor, 219
 Engine support fixture, 219
 Enrichment, 219
 Environmental Protection
 Agency (EPA), 219
 Equivalent resistance, 220
 Erasable programmable
 read-only memory
 (EPROM), 220
 Ergonomics, 220
 Ethanol, 222
 Ethylene glycol, 222
 Ethylhexanoic acid
 (2-EH), 379
 Ethyl tertiary butyl ether
 (ETBE), 222

- Evaporative (EVAP)
 - emission control system, 224
- EV battery charging
 - connectors, 224–225
- EV charging station, 225–226
- EV charging time, 226–227
- Event data recorder (EDR), 207
- EV heater core, 288
- EV paddle connector, 227
- Exhaust aftertreatment system (ATS), 227–228
- Exhaust brake, 228
- Exhaust gas analyzer, 228
- Exhaust gas recirculation (EGR), 207
- Exhaust gas sensor, 228
- Exhaust manifold, 229
- Exhaust pipe bending, 229
- Exhaust system, 229
- Exhaust system
 - hangers, 230
- Exhaust valve timing, 592
- Expansion tank, 230–231
- Extended core spark plug, 231
- External combustion engine, 231
- Extreme pressure (EP) additive, 219
- F**
- Factory-level scan
 - tools, 480
- Failure mode identifier (FMI), 115, 245
- Failure record, 234
- False lean, 234
- False rich, 234
- Fanstat, 234
- Farad, 234
- Faraday's Laws of
 - Electromagnetic Induction, 234–236
- Fast control area network (F-CAN), 236
- Fast idle solenoid, 236
- Fatigue, 236
- Federal test procedure (FTP), 256
- Feedback, 237
- Feeler gauge, 237
- Felling head, 237
- Fender, 237
- Fiberboard, 238
- Fiber optics, 238
- Field circuit, 238
- Field circuit
 - modulation, 238
- Field coils, 48, 238
- Field oriented control (FOC), 513
- Field relay, 238
- Fifth wheel, 238–239
- Fillet, 239
- Film strength, 239
- Filter, 239
- Final drive, 239
- Fire ring, 240
- Firewall, 240
- Firing interval, 307
- Firing line, 240
- Firing order, 240
- Firing section, 240
- Firing voltage, 240
- Flag, 240
- Flame point, 240
- Flank, 241
- Flash codes, 241
- Flash point, 241
- Flathead ICE, 241
- Flex fan, 241–242
- Flexible fuel vehicles (FFV), 237
- Flexplate, 242
- Float bowl, 242
- Floating car data (FCD), 236, 273
- Floating cellular data, 236
- Flooding, 242
- Floorboard, 242
- Flow parameters, 242
- Flow switch, 242
- Fluid coupling, 243
- Flux, 244
- Flux density, 244
- Flux lines, 244
- Flywheel, 244–245
- Foam inhibitors, 245
- Folding outside mirrors, 246
- Foot-pound, 246
- Force, 247
- Force coefficient, 247
- Ford Motor Company, 52
- Forestry machines, 248
- Forged, 248
- Forklift truck, 248–249
- Formed-in-place gasket (FIPG), 239
- Forward collision alert system, 249–250
- Forward control truck. *See* Cab-over-engine (COE)
- Fouling spark plug, 250
- Foundation brakes, 250–251
- Four-stroke cycle (4-stroke cycle), 2–6, 251
- Four-wheel-drive (4WD)
 - shift motor, 7
- Four-wheel drive (4WD)
 - vehicle, 7, 53, 58, 251, 426, 565
- Four-wheel steering, 251–252
- Four-wire oxygen sensor, 252
- Fractured connecting rod, 252
- Frame design, 253
- Frame-ground circuit, 253
- Free electrons, 253
- Free-floating piston pin, 253
- Free vibration, 254
- Freewheeling clutch, 390
- Freeze frame, 254
- Freon refrigerant, 129
- Frequency, 255
- Frequency modulation (FM), 245
- Friction, 255
- Friction clutch, 255
- Front axle disconnect (FAD), 233
- Front/rear split braking system, 255–256
- Front-wheel-drive (FWD)
 - vehicle, 58, 169–170, 262

- Fuel, 256
- Fuel cell, 257
- Fuel compensation
 - sensor, 257
- Fuel gauge circuit, 257
- Fuel injection, 257
- Fuel line, 257
- Fuel mechanical pump, 258
- Fuel pressure regulator, 257
- Fuel rail, 259
- Fuel system, 259
- Fuel tank, 260
- Fuel trim, 260
- Fuel trim monitor, 260
- Fulcrum, 260
- Full driving automation, 260
- Full-floating axle, 260
- Full hybrid, 260–261
- Functional check
 - procedure, 261
- Functional monitoring, 261
- Fuse, 261
- Fuse box, 261
- Fused jumper wire, 261
- Fusible link, 261–262
- G**
- Galling, 265
- Gap switch, 265–266
- Garter spring, 266
- Gas analyzer, 266
- Gasket, 266
- Gas laws, 266
- Gasohol, 266
- Gasoline, 267
- Gasoline direct injection
 - (GDI), 267–268
- Gauss, 267
- Gauss gauge, 267
- Gay-Lussac's law, 267
- G-Coolants, 265
- Gearbox, 268
- Gear ratio, 268
- Gear reduction, 268
- Gear reduction
 - starter, 268
- Gears, 268
- Gearset, 269
- Gel battery, 269
- General Motors (GM), 52, 122, 168, 386
- Generation II Eaton Fuller
 - Roadranger truck transmissions, 57
- Generator. *See* Alternator; DC Generator
- Geometric centerline, 269
- Geometry, 269
- Glad hands, 269–270
- Global positioning system
 - (GPS), 273
- Glow plug, 271
- Glow plug diagnosis, 271
- Glow plug electronic
 - controller, 272
- Glow plug thermal
 - controller, 272
- Governor mechanism, 272–273
- Grain alcohol, 222
- Gram, 273
- Graphite, 274
- Graticule, 274
- Grease, 274
- Gross combined weight
 - rating (GCWR), 267
- Gross horsepower, 275
- Gross vehicle weight rating
 - (GVWR), 51, 276
- Ground, 275
- Grounded circuit, 276
- Ground prong, 276
- H**
- Half shaft, 279
- Half-wave rectification, 279
- Hall-effect material, 456
- Hall-effect sensor/switch, 279–280
- Hall-effect sensor test, 280
- Halogen light bulb, 280
- Handbrake/e-brake, 398
- Harmonic balancer, 280–281
- Harness connectors, 281
- Harness routing
 - diagram, 281
- Headliner, 282
- Head Up Display
 - (HUD), 294
- Heat, 282
- Heat crossover, 282
- Heated mirrors, 284
- Heated rear window
 - defroster, 284–285
- Heated seats, 285
- Heat engine, 283
- Heater core, 285
- Heater hoses, 285
- Heating, ventilation, and
 - air conditioning (HVAC) system, 435
- Heat of compression, 284
- Heat range, 283
- Heat riser, 283
- Heat shield, 283
- Heat shrink tubing, 283
- Heat sink, 284
- Heat-treated truck
 - frame, 284
- Heat value of liquid, 284
- Heave, 285
- Heavy-duty coil spring
 - clutches, 423
- Heavy-duty on-board
 - diagnostics (HD-OBD), 51, 88, 282
- Height sensing brake
 - proportioning valve, 285
- Helical gear, 285–286
- Hemispherical combustion
 - chamber, 286
- Hendrickson equalizing
 - bar, 286
- Hertz, 286
- Hesselman helical loop, 286
- HEV heater core, 288
- High driving
 - automation, 289
- High energy ignition
 - (HEI), 285
- High-pressure common rail
 - (HPCR) diesel fuel injection, 289–290
- High-side drivers
 - (HSD), 293
- High-voltage buffer
 - zone, 290
- High-voltage (HV)
 - disconnect, 290

- High-voltage (HV)
 - electrical spark, 3
- Highway Driving Assist, 398, 399
- Homogeneous, 291
- Honda V2 industrial
 - engine, 165–166
- Hood, 291
- Hooke's law, 291
- Horn, 291
- Horsepower, 292
- Hotchkiss rear axle design, 292–293
- Housing bore diameter, 293
- Hub units, 293
- Hughes Electronics
 - Corporation, 386
- Hunting gears, 294
- Hybrid air cooling, 294
- Hybrid battery pack, 294
- Hybrid driver ready light, 294–295
- Hybrid electric vehicle (HEV), 20, 21, 37, 260–261, 287–288, 363, 375, 512
- Hybrid engine-starting
 - mode, 295
- Hybrid ground fault
 - interrupter, 295
- Hybrid high-voltage
 - system, 295
- Hybrid low-voltage
 - system, 295
- Hybrid master warning
 - light, 295
- Hybrid maximum
 - voltage, 295
- Hybrid motor-generator, 295
- Hybrid nominal operating
 - voltage, 296
- Hybrid Organic Acid
 - Technology (HOAT), 290–291
- Hybrid power display, 296
- Hybrid power
 - splitter, 296
- Hybrid refrigerant
 - cooling, 296
- Hybrid water cooling, 296
- Hydraulically actuated
 - electronic unit injection (HEUI), 286–287
- Hydraulically operated
 - clutch, 297–298
- Hydraulic brakes, 96–97
- Hydraulic control unit (HCU), 7, 8
- Hydraulic force
 - formula, 296
- Hydraulics, 298
- Hydraulic valve lifter, 297
- Hydroboost brakes, 242, 298
- Hydrocarbons (HC), 281, 298
- Hydrocracking, 298
- Hydrogen, 298
- Hydrogen hybrid, 299
- Hydrokinetic, 299
- Hydrometer, 299
- Hypoid gearsets, 299–300
- Hysteresis, 300
- I**
- I-beam steering axle, 303
- Identification (ID)
 - numbers, 310
- Idle, 305
- Idle air control (IAC), 303
- Idle jet, 305
- Idle load control (ILC), 309
- Idler arm, 305–306
- Idle speed control (ISC), 317
- Idle stop mode, 305
- Igniter, 306
- Ignition circuit, 306
- Ignition coil, 306–307
- Ignition coil output test, 307
- Ignition control (IC), 304
- Ignition control module (ICM), 305
- Ignition interval, 307
- Ignition point/autoignition
 - diesel fuel, 307
- Ignition switch, 307
- Ignition system, 307–308
- Ignition timing, 308
- Immobilizer, 309–310
- Impeller, 310
- Independent rear suspension (IRS), 310
- Independent suspension, 310
- Indicated horsepower (IHP), 308–309
- Indicated mean effective
 - pressure (IMEP), 309
- Indirect diesel injection (IDI), 305
- Indirect injected (IDI)
 - diesel, 419, 420
- Indirect injection (IDI), 5, 169
- Inductance, 310
- Induction, 311
- Inductive pickup, 311
- Inductive reactance, 311
- Inertia, 311
- Inertia weight, 158
- Infinite resistance, 311
- Infrared digital handheld
 - noncontact thermometer, 311–312
- Infrared radiation, 312
- Injection nozzle, 312
- Injector, 313
- Injector pulse width, 313
- Inorganic additive
 - technology (IAT), 303
- Inspection maintenance (I/M) flags, 240
- Instant center, 313
- Instrument cluster, 313
- Insulator, 313–314
- Intake air temperature (IAT) sensor, 303–304
- Intake manifold, 314
- Intake valve timing, 592–593
- Integral steering gear
 - steering linkage, 519–520
- Integrated circuit (IC), 304
- Integrated-electro-hydraulic braking
 - system (I-EHB), 7, 8

Intelligent transportation systems (ITS), 318
 Intelligent vehicle highway system (IVHS), 318
 Intelligent vehicle technologies (IVT), 314, 318
 Intensifier piston, 42
 Interaxle differential, 314–315
 Intercooler, 315, 316
 Interference angle, 316
 Interlock, 316
 Intermittent problem, 316
 Internal combustion engine (ICE), 395
 Internal mode switch (IMS), 492
 International Organization for Standardization (ISO), 317
 Inversion valve air brakes, 507–508
 Inverter circuit, 316
 Ion, 317
 Ionize, 317
 Ion-sensing ignition system, 317
 Iron, 317
 Isooctane, 318

J

Jack, 321
 Jackknife, 321
 Jake brake, 322
 Jamb switch, 322
 Jerk pump, 322
 Jet, 322
 Jidoka, 322
 Jounce, 322
 Jump box, 322, 323
 Jumper cables, 324
 Jumper wire, 261, 324
 Jump start, 323–324
 Junction block, 325
 Just-in-time (JIT), 327

K

Kaizen, 327
 Kanban, 327–328
 Karman vortex, 328

Keep alive memory (KAM), 327
 Kerosene, 328
 Keyless entry, 328
 Kickdown (detent) lever, 328–329
 Kickdown switch, 329
 Kilo, 329
 Kilowatts, 329
 Kinematic formulae, 329–330
 Kinematics, 330
 Kinematic viscosity, 330
 Kinetic energy, 330
 Kingpin, 330–331
 Kingpin inclination (KPI) angle, 310, 332
 Kirchhoff's first law of current, 332
 Kirchhoff's second law of voltage drops, 332
 Knock Sensor (KS), 332


L

Ladder frame, 335
 Lambda sensor, 335
 Landing gear, 335, 336
 Lane centering control (LCC), 338
 Lane departure, 336–337
 Lane departure warning (LDW), 336–337
 Lane keep assist switch, 337
 Lateral runout, 338
 Leaf spring, 338–339
 Leaf spring suspension system heavy truck, 339
 Lean methods, 338
 Lean misfire, 338
 Left-hand rule, 340
 Lenz's law, 340
 L-Head, 341
 Lift, 342
 Lift axle, 342
 Lifter, 342
 Lifter pump-up, 342
 Lift pump, 342
 Light detection and ranging (Lidar), 341–342

Light emitting diodes (LEDs), 339–340
 Lightning, 343
 Limited slip differential (LSD), 348–349
 Liner, 344
 Lines of force, 345
 Liquefied natural gas (LNG), 345
 Liquid crystal display (LCD), 338
 Liquid petroleum gas (LPG), 348
 Lithium grease, 345
 Lithium-ion (Li-ion) battery, 343–344
 Load, 345
 Load devices, 345
 Loader, 346
 Loadstone, 346
 Location grid, 346
 Locking differential, 347
 Locking hubs, 347–348
 Lock-up clutch, 348
 Long block, 348
 Low oil level indicator circuit, 348
 Low-voltage disconnect (LVD), 351–352
 Lubricant, 349
 Lubrication system, 349–350
 Lubricity, 350
 Luminosity timing meter, 351

M

M-85, 353
 MacPherson strut suspension, 353, 365
 Magnetic coil gauge, 354
 Magnetic crankshaft position sensors, 354
 Magnetic field, 345, 354–355
 Magnetic field intensity, 355
 Magnetic flux, 345, 355
 Magnetic pulse generator, 355
 Magnetic repulsion, 356
 Magnetic timing, 356

- Magnetism, 356
- Magneto ignition, 356–357
- Magnetorheological (MR), 367–368
- Main Bearing Journals, 357
- Manifold absolute pressure (MAP), 116, 358, 505
- Mass air flow (MAF) sensor, 354
- Master cylinder, 143, 358–359, 457
- Match mounting tires, 360
- Material safety data sheet (MSDS), 482
- Matter, 360
- Mean effective pressure (MEP), 362
- Measurement prefixes, 360
- Measuring system, 158
- Mechanical efficiency, 360–361
- Mechanical fuel injection nozzles, 361
- Mechanical returnless fuel system (MRFS), 368
- Mechanical unit injector (MUI), 580
- Medium-duty truck hydraulic ABS, 361–362
- Memory seat, 362
- Message identifier (MID), 363
- Metering valve, 362
- Methanol, 362
- Methyl cyclopentadienyl manganese tricarbonyl (MMT), 364
- Methyl tertiary butyl ether (MTBE), 368
- Microorganisms, 363
- Mild hybrid, 363
- Mild steel, 363
- Miscibility, 363
- Miscible, 363
- Misfire, 364
- Misfire monitor, 364
- Mobile ad hoc networks (MANETs), 358, 594
- Mobile data, 364
- Mobility, 364–365
- Modified strut suspension, 365
- Modular fuel sender, 366
- Module, 366
- Module programming, 366
- Molybdenum (MO), 364
- Moment, 247
- Monitor controller, 366
- Monitors, 367
- Monograde, 367
- Motor assist mode, 367
- Motorcycle, 12, 367
- Motor generator, 367
- Motor-generator armature, 367
- Motor octane number (MON), 366
- Mubea-type cooling system hose clamp, 443
- Muda, 368
- Muffer, 368
- Muffer clamp, 369
- Multigrade/multiviscosity oil, 369
- Multimeter. *See* Digital multimeter
- Multiplexing, 369
- Multiplex integrated control (MIC), 363
- Mura, 369
- Muri, 369
- Mutual induction, 307, 370
- N**
- Natural frequency, 373
- Naturally aspiration, 373
- Navigation system, 373
- Needle bearing, 373
- Needle valve, 373
- Negative temperature coefficient (NTC), 378
- Neoprene, 374
- Net brake horsepower, 374
- Net valve lift, 374
- Network, 374
- Neutral safety switch, 374
- Neutral steer, 374
- Neutron, 375
- Nickel-cadmium cell (NiCd), 375
- Nickel metal hydride battery (NiMH/ Ni-MH), 375
- Nickel oxide hydroxide (NiOOH), 375
- Night vision, 375
- Nitriding, 376
- No driving automation, 376
- Noid test light, 376
- Noise suppressor, 376
- No-load voltage, 376
- Nominal opening pressure (NOP), 377
- Non-continuous monitor, 376
- Non-hunting gearset, 377
- Non-interference ICE, 377
- Nonvolatile memory, 377
- Normally aspiration, 377
- Nose, 378
- Nose circle, 378
- NOx. *See* Oxides of nitrogen
- Nucleus, 378
- 
- OBD II communications anomaly list, 380
- OBD II Drive Cycle, 380
- Occurrence count (OC), 116
- Octane rating, 380
- Odometer, 380
- Odometer memory chip, 380
- Offset, 381
- Off-vehicle balancing, 612–613
- Ohm, 381
- Ohmmeter, 381
- Ohm's law, 381
- Ohm's law formula, 381
- Ohm's law general rules, 382
- Ohm's law solving circle, 383
- Oil control ring, 383
- Oil cooler, 383
- Oil-filled truck hub, 383
- Oil pump, 384

- Oil slinger, 384
- Omega (Ω), 385
- On-Board Diagnostic (OBD), 113–114, 379
- On-Board Diagnostics
 - Generation II (OBD II), 88, 123, 132, 379
- One-wire circuit, 385
- One-wire oxygen sensor, 385
- OnStar system, 386
- On-vehicle balancing, 612–613
- Open circuit, 386–387
- Open-circuit voltage test, 387
- Open diode, 387
- Opening ramp, 387
- Open-loop mode, 387
- Optical sensor, 387
- Optical signal
 - generator, 388
- Order (vibration), 388
- Organic acid technology (OAT), 168
- Organic acid technology (OAT) ethylene glycol-based antifreeze, 379
- Original equipment manufacturers (OEMs), 366, 381
- O-Ring, 388
- Oscilloscope, 388
- O₂ sensor, 379
- Otto-cycle engine, 389
- Out of Limits, 389
- Output drivers, 389
- Outputs, 389
- Overdrive, 389
- Overhang, 389
- Overhead ICE
 - camshaft, 389
- Overlap, 389–390
- Over limits digital multimeter (OL DMM) symbol, 384–385
- Overrunning clutch, 390
- Oversquare engine, 390
- Oversteer, 390
- Oxidation, 390
- Oxidation catalysts, 390
- Oxidation reaction, 390
- Oxides of nitrogen (NOx), 378, 391, 481
- Oxygenated fuels, 391
- Oxygen sensor, 228
- Ozone, 391
- P**
- Packing, 393
- Panhard arm/bar, 393
- Paraffin, 393
- Parallel circuits, 393–394
- Parallel hybrid, 395
- Parallelism, 395
- Parallelogram integral steering gear, 519–520
- Parallelogram steering system, 518–519
- Parallelogram type, 518–519
- Parallel wire, 395
- Parameter group number (PGN), 115, 474
- Parameter identifier (PID), 405–406
- Parameters
 - identification, 479
- Parasitic load/draw, 396
- Park, 396
- Park control valves, 396–397
- Parking assist systems, 398
- Parking brake, 398
- Partial driving automation, 398–399
- Particulate matter (PM), 188, 399
- Parts per million (PPM), 419
- Pascal's Law, 399
- Passive keyless entry, 400
- Passive sensor, 400
- Passive systems, 400
- Passive wheel speed sensor (WSS), 615–616
- Peak-and-hold fuel injector waveform, 402
- Pedestrian collision
 - mitigation braking, 402
- Pendulum belt retractor, 402
- Pentroof combustion chambers, 402–403
- Permanent magnet (PM), 412, 415–416
- Permanent magnet AC (PMAC), 412–413
- Petrochemical, 403
- Phasing, 191
- Phosphate hybrid organic acid technology (PHOAT), 403
- Photoelectricity, 403–404
- Pickup coil, 404–405
- Piezoelectric principle, 406
- Piezo-resistive sensors, 406–407
- Piezo-resistor chip, 407
- Pigment, 407
- Pilot jet, 407
- Ping, 407
- Pinion, 239
- Pinion gear, 407
- Pintle nozzle, 407–408
- Piston, 408–409
- Pitch, 409
- Pitch circle diameter (PCD), 400–401
- Planar zirconia oxygen sensor, 409
- Planetary gearset, 409–411
- Plasma screen, 411
- Plastigage™, 411
- Plate strap, 412
- Plug and play (PNP) fuel injector
 - waveform, 413
- Plug-in hybrid, 412
- Polarity, 413
- Pole, 413
- Polychloroprene, 374
- Poppet valves, 413
- Positive crankcase ventilation (PCV), 401
- Positive temperature coefficient (PTC), 427

- Potential, 413
 - Potential difference, 413–414
 - Potential energy, 414
 - Potentiometer, 414
 - Power, 415
 - Power balance test, 415
 - Power distribution
 - diagram, 415
 - Power divider, 415
 - Power door locks, 415–416
 - Power seats, 416
 - Power steering drive belt system, 416
 - Power steering pump, 416–417
 - Power steering rack-and-pinion gear, 417–418
 - Power steering systems, 418
 - Power takeoff (PTO), 427
 - Powertrain control module (PCM), 206, 401
 - Power transfer unit (PTU), 58
 - Power windows, 419
 - Pre-adjusted hubs, 419
 - Prechamber, 141, 419
 - Predictive systems, 420
 - Pre-ignition, 420–421
 - Pressure differential valve, 421–422
 - Pressure-limiting (ratio) valve, 422
 - Pressure plate, 422–423
 - Pressure sensor, 424
 - Primary coil windings, 424
 - Primary ignition circuit, 424
 - Primary ignition scope pattern, 424
 - Principle direction of force (PDOF), 1–2, 401
 - Printed circuit, 424
 - Process, 424
 - Process map, 425
 - Processor, 425
 - Program, 425
 - Programmable read-only memory (PROM), 425
 - Propane. *See* Liquid petroleum gas (LPG)
 - Propeller shaft, 191–193, 425–426
 - Proportioning valves, 426
 - Propylene glycol, 426
 - Proton, 427
 - Pro-Torq® spindle nut, 427
 - P-type material, 427
 - P-type silicon, 486
 - Pulse, 427
 - Pulse generators, 427
 - Pulse train, 427
 - Pulse width, 428
 - Pulse width modulation (PWM), 428–429
 - Pump, 428
 - Pumping losses, 428
 - Push-pull dual-circuit model, 396
 - Pushrod, 428
- Q**
- Quarter panel, 431
 - Quench areas, 432
 - Quick-release valves, 432
 - Quill, 432–433
- R**
- Rack, 436
 - Rack-and-pinion gearbox, 520–521
 - Rack-and-pinion steering. *See* Power steering rack-and-pinion gear
 - Radar, 436
 - Radar cruise control, 15
 - Radial, 437
 - Radial engine, 437
 - Radial tire, 438
 - Radiation, 439–440
 - Radiator, 440–441
 - Radiator fan shroud, 442
 - Radiator hose, 442
 - Radiator hose clamp, 443
 - Radio frequency interference (RFI), 462
 - Radius, 443
 - Radius arm/rod, 444
 - Rail diesel fuel injection, 141–142
 - Rain-sense module (RSM), 444–445
 - Rain-sense wiper systems, 444–445
 - Ram air, 445
 - Ram duct, 445
 - Ramp closing, 134
 - Ramps, 445
 - Random access memory (RAM), 445
 - R134a refrigerant, 435
 - Rationality, 445
 - Rationality monitoring, 446
 - Reactance, 446
 - Read-only memory (ROM), 446
 - Rear axle, 446
 - Rear axle ring, 239
 - Rear drive unit (RDU), 58
 - Rear spacing, 67
 - Rearview mirror, 446
 - Rear-wheel disc brakes, 446–447
 - Rear-wheel drive (RWD), 470
 - Rebound, 447
 - Recapped tire, 447
 - Reciprocating engine, 447
 - Recirculating-ball steering gear, 447–448
 - Recombinant battery, 448
 - Recombination electrolyte technology, 448
 - Rectifier, 448
 - Reductant, 166–167. *See also* Diesel exhaust fluid
 - Reed tachometer, 449
 - Reed valve, 449
 - Refer, 449–450
 - Reference voltage (Vref), 450
 - Refining oil, 450
 - Reflector, 451
 - Reformulated gasoline (RFG), 451
 - Regenerative braking, 451–452
 - Reid vapor pressure (RVP), 469

- Relative humidity, 452
- Relay, 452–453
- Relay rod/drag link, 126, 453–454
- Relay valves, 454–455
- Release bearing, 455–456
- Reluctance, 456
- Reluctor, 456–457
- Remolding tires. *See* Retreading a Tire (Recap)
- Remote start system, 457
- Replenishing port, 457
- Research octane number (RON), 366, 467–468
- Resistance, 458
- Resistance factors, 458
- Resistance to bending moment (RBM), 446
- Resistivity, 72
- Resistors, 458
- Resistor-type spark plug, 458
- Resolver, 459
- Resolving center, 459
- Resonance, 459–460
- Resonator, 460
- Retarder. *See* Electric Brake Retarder
- Retread, 447
- Retread identification, 460
- Retreading a Tire (Recap), 461
- Reverse, 461
- Reversible kingpin, 462
- Revolutions per minute (RPM), 94, 469
- Reynolds number, 462
- RFG. *See* Reformulated gasoline
- Rheology, 462
- Ricardo Comet 5 piston, 141
- Ride height adjustment, 462
- Ridge reamer, 463
- Right-hand rule, 463
- Ring and pinion, 464
- Ring gap, 464
- Rise time, 464
- Road draft tube, 464
- Rocker arm geometry, 465
- Rocker arm ratio, 465
- Roll bar, 465
- Roll center, 465
- Roller chain, 465
- Roller/tappet lifter, 466
- Rollover, 466–467
- Rollover threshold, 467
- ROM. *See* Read-only memory
- Roots type, 468
- Rotor, 469
- Rotor gap voltage, 469
- Run-flat tire, 469
- Rust inhibitor, 469
- R1234yf refrigerant, 435
- S**
- Sac cavity, 473
- SAE/ATA J1587/J1939/J1708 codes and protocols, 474
- SAE Electric Vehicle (EV) Charging Standards, 474–475
- SAE horsepower, 475
- SAE mobilus, 476
- SAE viscosity grade, 476
- Safety data sheets (SDS), 482
- Sag frame damage, 476
- Satellite radio, 477
- Saturated switch fuel injector waveform, 477
- Saw cut loop detectors, 477–478
- Scaling a race car, 478
- S-cam brake system, 479
- S-cams, 478, 498
- Scan data, 479
- Scan tool, 479–480
- Scan tool snapshot, 480
- Schrader valve, 480
- Screw-type clamps, 443
- Scrub radius, 481–482
- Scuffing, 482
- Sealed axle bearing, 482–483
- Sealed beam headlamp, 483
- Sealed lead-acid (SLA) battery, 166
- Seat memory module, 483
- Seat position sensor, 483
- Secondary battery, 483
- Secondary coil winding, 483
- Secondary ignition circuit, 484
- Secondary ignition scope pattern, 484
- Secondary nonresistance wire, 484
- Secondary pickup, 484
- Secondary wire, 484
- Section modulus, 484
- Sediment, 484
- Segmented contacts, 48
- Seize, 484
- Selective catalytic reduction (SCR), 227–228, 481
- Selector mechanism, 485
- Self-adjusting mechanism, 195–196
- Self-induction/self-inductance, 485
- Semiconductor, 485
- Semiconductor doping, 486
- Semi-trailer, 486
- Sensor, 486–487
- Sequential fuel injection (SFI), 491
- Sequential hydro-supercharging system (SHS), 569
- Serial communication/serial data, 487
- Series circuit, 487–488
- Series hybrid, 488–489
- Series motor, 489
- Series-parallel circuit, 489
- Series-parallel hybrid, 490
- Series parallel switch, 490
- Series-wound motor, 490
- Serpentine belt, 490
- Serpentine belt tensioner, 83
- Service brake chamber, 490
- Service brakes, 491
- Servomechanism, 491
- Setback angle, 491
- Shackle, 491
- Shift, 491

- Shift collar, 491
 - Shift fork, 491
 - Shift selector, 492
 - Shock absorbers, 493
 - Short block, 494
 - Short circuit, 494
 - Shorted diode, 494
 - Short-term/long-term fuel trim, 494–495
 - Short-to-ground, 495
 - Short-to-voltage, 496
 - Siamese ICE cylinders, 496
 - Side blind zone alert system, 497
 - Sidesway frame damage, 497
 - Silent chain, 497
 - Silicon, 486
 - Single-cardan joint, 581–582
 - Single grade, 497
 - Single motor-generator hybrid, 497
 - Single overhead camsha_ (SOHC), 389
 - Single-phase current, 497
 - Single-phase voltage, 498
 - Single-reduction axle, 498
 - Skid, 498
 - Slack adjuster, 498–499
 - Sleeve. *See* Liner
 - Slip angle, 499–500
 - Slippage, 501
 - Slip yoke, 500–501
 - Sludge, 501
 - Sludge trap, 502
 - Smog, 502
 - Smoke, 502. *See also* Black smoke; Blue smoke; White smoke
 - Snubber, 502
 - Society of Automotive Engineers (SAE), 473–474
 - Sodium-cooled exhaust valve, 502
 - Solder, 502
 - Soldering, 502
 - Soldering gun, 502
 - Soldering iron, 502
 - Solenoid, 503
 - Source Address (SA), 113–115
 - Spark gap, 503
 - Spark ignition, 2–4
 - Spark knock, 503. *See also* Detonation
 - Spark line, 503
 - Spark plug, 503–504
 - Spark scatter, 504
 - Spark tester, 504
 - Spark voltage, 504
 - Specific fuel consumption. *See* Brake specific fuel consumption (BSFC)
 - Specific gravity, 504
 - Specific gravity battery test, 504–505
 - Speed density, 505
 - Speedometer, 505
 - Spindle, 505
 - Spiral bevel gearset, 505–506
 - Split safety lock wheel rim, 506
 - Spring brake chamber, 506–507
 - Spring brake control valve, 507–508
 - Spring-brake park control valve, 396, 397
 - Springs, 508–509
 - Sprung/unsprung weight ratio, 510
 - Sprung weight, 510
 - Spur gear, 510
 - Square engine, 510
 - Stabilizer bar, 510–511
 - Stall, 512
 - Star configuration, 512
 - Starter brushes, 512
 - Starter generator, 512–513
 - Starter motor, 513–514
 - Starter motor 12/24_V protocol, 514
 - Starter relay, 515
 - Starter solenoid, 515
 - Starting system, 516
 - Star wheel, 512
 - State of charge (SOC), 75, 299
 - Static electricity, 516–517
 - Steering angle alignment, 395
 - Steering axis inclination (SAI), 310, 476–477
 - Steering column, 218–219
 - Steering geometry, 517
 - Steering knuckle, 517–518
 - Steering system, 518–521
 - Stepper motor, 521
 - Stoichiometric air-fuel mixture, 521
 - Stopping distance, 522
 - Strain-gauge MAP sensor, 522
 - Strategy-based diagnostics, 522
 - Stroboscopic, 522
 - Stroke, 522
 - Subsystem identifier (SID), 496
 - Supercharger, 523
 - SuperCruise, 523
 - Superglue, 42
 - Supplemental inflatable restraint (SIR) system, 22–23
 - Supplemental restraint system (SRS), 14, 134
 - Surface finish, 523
 - Suspect parameter number (SPN), 114, 115
 - Suspension system, 330–331, 523–524
 - Sway bar, 45, 510–511
 - Sweep rate, 524
 - Switch, 279–280
 - Synchronizer, 90, 524–525
 - Synchronous, 525
 - Synthetic oil, 525
 - System wiring diagram, 526
- T**
- Tachometer, 529
 - Tail lamp, 529
 - Tailpipe, 530
 - Tail shaft, 529
 - Tall firing line, 530
 - Tandem drive axle, 530

- Tandem master cylinder.
 See Dual master cylinder
- Tank sending unit, 531
- Tape player, 531
- Tapered roller bearings, 531–532
- Tappet. *See* Cam follower; Lifter
- Task manager, 532
- Technical assistance
 hotlines, 534
- Technical service bulletins (TSBs), 568
- Technology and
 Maintenance Council (TMC), 553
- Telematics, 314, 534
- Telematic satellite
 navigation, 534
- Telltale light, 534
- Temperature, 534–535
- Temperature gauge
 circuit, 535
- Temperature probe, 178
- Terminal, 535
- Tertiary-amyl methyl ether (TAME), 530
- Tesla autopilot, 535
- Test light (12 V), 535–536
- Tetraethyl lead, 536
- Tetrafluoropropylene, 435
- Thermal cracking, 153
- Thermal efficiency, 536–537
- Thermal expansion, 537–538
- Thermal loading, 538
- Thermistor, 538
- Thermodynamic cycle, 538
- Thermodynamics, 538–539
- Thermoelectricity, 539
- Thermoelectric
 principle, 539
- Thermosiphon coolant
 circulation, 539
- Thermostat, 539–540
- Thermostatic air cleaner (TAC), 529
- Thickness gauge, 237
- Thixotropic, 540
- Three-pedal system, 540–541
- Three-quarter-floating axle, 541
- Three-wire oxygen sensor, 541
- Threshold monitoring, 541–542
- Throating, 542
- Throttle, 542
- Throttle body, 542
- Throttle body electronic fuel injection, 542
- Throttle body injection (TBI), 532
- Throttle cable, 542
- Throttle position sensor (TPS), 562
- Throttle position (TP)
 switch, 561
- Throttle relaxer, 542
- Throttle valve, 542–543
- Throttle valve detent control, 543
- Through-drive differential
 power flow, 543
- Thrust angle, 543–544
- Thrust bearing, 545
- Tie rod, 545
- Timing, 546
- Timing belt, 546
- Timing chain, 546–547
- Timing light, 547
- Tinning, 547
- Tire, 547–548
- Tire bead, 549
- Tire belt, 549
- Tire blowout, 549–550
- Tire body ply, 550
- Tire cap ply, 550
- Tire identification number (TIN), 460
- Tire inner liner, 551
- Tire ply rating, 551
- Tire pressure monitoring system (TPMS), 561–562
- Tire pressure sensor, 551
- Tire regrooving, 551
- Tire retread/recap, 552
- Tire sidewall, 552
- Tire sipes and grooves, 552
- Tire stress cycles, 552–553
- Tire/wheel runout, 553
- Titania oxygen sensor, 553
- Toe, 554
- Toe-out on turns (TOOT), 554–555
- Top dead center (TDC), 2–4, 168–169, 198, 522, 533–534
- Torque, 555–557
- Torque bars, 560
- Torque converter, 557–558
- Torque converter clutch (TCC), 532–533, 557
- Torque converter formula, 558–559
- Torque differential, 560
- Torque rise, 559
- Torque steer, 559
- Torque tube, 559
- Torque wrench, 560
- Torsional (vibration)
 damper. *See* Harmonic balancer
- Trace, 562
- Tracing powder/chalk
 diagnostic test, 562
- Track rod. *See* Tie rod
- Traction, 562
- Traction control system (TCS) car and light truck, 533
- Tractor, 562–563
- Tractor protection
 valve, 563
- Traffic-sign recognition, 563
- Trailer, 331, 563
- Trailer hand brake, 563–564
- Trailer tracking, 564
- Trailing-arm
 suspension, 564
- Transaxle, 564–565
- Transducer, 565
- Transfer case, 565
- Transformer, 566
- Transistor, 566
- Transmission, 566

- Transmission control module (TCM), 492, 533
- Transponder, 566
- Transportation
 - Refrigeration Unit (TRU), 449–450
- Transverse engine, 566
- Tread depth, 567
- Tread separation, 567
- Trigger, 567
- Trimetal engine bearing material, 568
- Triple motor-generator hybrid, 568
- Truck and bus air brakes, 610–611
- Truck frame, 568
- Tufriding, 568
- Turbine, 569
- Turbocharger, 20, 569–570
- Turbulence, 5–6
- Turning radius, 554, 570
- Turntable, 570
- Twin countershafts, 571
- Twist, 571
- Two-gear reduction axle, 571
- Two-pedal system, 572
- Two speed axle, 572
- Two-stroke engine, 572–573
- Two-wheel drive (2WD), 6, 53
- Two-wire oxygen sensor, 573
- Type A misfires, 573
- Type B misfires, 573
- U**
- Ultra-capacitor module, 577
- UltraShift truck transmission, 578
- Ultrasonic (sensor), 578
- Ultrasonic sensors parking assist system, 578–579
- Ultrasound, 579–580
- Undercarriage, 580
- Undersquare engine, 580
- Understeer, 580
- Uniform Tire Quality Grading System (UTQGS), 582
- Unit fuel injector, 580
- Unitized hub, 580–581
- Unitized seals, 581
- Universal joint (U-joint) operation, 581–582
- Unladen weight, 158
- Unsprung weight, 582
- Urea, 166–167. *See also* Diesel exhaust fluid
- US Department of Transportation (DOT) issues, 99
- V**
- Vacuum, 585–586
- Vacuum fluorescent display (VFD), 597
- Vacuum gauge, 587
- Vacuum pump, 587
- Valence, 587
- Value stream map (VSM), 604
- Valve, 587
- Valve checking, 129
- Valve covering orifice (VCO) diesel fuel injector, 595
- Valve face, 587–588
- Valve float, 588
- Valve guide, 588
- Valve keeper, 588–589
- Valve lift, 589
- Valve lifter, 589–590
- Valve lift measurement, 589
- Valve overlap, 590
- Valve regulated lead-acid (VRLA) battery, 604
- Valve regulated sealed lead-acid (VRSLA), 448
- Valve retainer, 590
- Valve seat, 590
- Valve spring, 590
- Valve spring tester, 590, 591
- Valve stem, 591
- Valve stem seal, 591
- Valve timing, 591–593
- Valve train, 594
- Vapor, 594
- Vapor lock, 594
- Variable damping shocks, 594
- V-belt, 594–595
- Vehicle identification number (VIN), 598–599
- Vehicle re-identification methods, 595
- Vehicle speed sensor (VSS), 14, 604
- Vehicle telematics, 595–596
- Vehicle-to-Infrastructure (V2I), 585
- Vehicle-to-vehicle (V2V), 585
- Vehicle tracking, 596
- Vehicle (truck) weight distribution equations, 596–597
- Vehicular ad hoc network (VANET), 594
- Velocity, 597
- Venturi, 597
- Vent valve, 90
- Vertical split system, 255–256
- Vibrations, 597–598
- Video vehicle detection systems, 598
- Viscosity, 599
- Viscosity index (VI) improvers, 599–600
- Viscous coupling, 600
- Viscous fan clutch, 601
- Volatile memory, 602
- Volatility/volatile, 602
- Volt, 602
- Voltage, 57–58, 310, 602
- Voltage drop measurement/voltage drop tests, 602–603
- Voltage regulator, 603
- Voltmeter, 603
- Volt-ohm-milliammeter (VOM). *See* Digital multimeter
- Volts per division, 603
- V-ref, 603
- V-twin, 367

W

- Walking beam truck suspension. *See* Hendrickson Equalizing Bar
- Wander, 607
- Wankel engine, 607
- Warm-up cycle, 607
- Warning light, 607
- Warp, 608
- Wastegate, 608
- Waste spark, 608
- Waste-spark ignition, 608
- Water-cooled system, 608.
See also Cooling system
- Water jacket, 609
- Water pump, 609
- Watt rating, 610
- Watt's law, 610
- Watt's linkage, 610
- Waveform, 610
- Weather strip, 610
- Web, 610
- Wedge brake design, 610–611
- Wedge-shaped combustion chamber, 611
- Weight transfer, 611
- Welch plug, 611
- Wet clutch, 611
- Wet liner, 344. *See also* Liner
- Wet sump, 611
- Wet weight, 158
- Wheatstone bridge, 612
- Wheel, 612
- Wheel balancing, 612–613
- Wheelbase, 616
- Wheel cylinder, 613–614
- Wheel disc, 614
- Wheel hop, 615
- Wheel offset, 615
- Wheel rim, 615
- Wheel shimmy, 615
- Wheel speed sensor, 615–616
- Wheel spin, 616
- Wheel well, 616
- White smoke, 617
- Wideband oxygen sensor, 35, 617
- Wide-open throttle (WOT), 621
- Windshield, 617–618
- Windshield washers, 618
- Windshield wipers, 618
- Wind tunnel, 617
- Windup. *See* Axle windup
- Wire, 618
- Wire code identification system, 618
- Wire gauge, 618
- Wireless vehicle safety communications telematics (WVSCT), 621–622
- Wire protection device, 619
- Wiring diagrams, 619
- Wiring harness, 619
- Wiring schematic, 619
- Wiring splices, 619
- Work, 619–620
- Worm gear steering gears, 620
- Wound stator, 625

Y

- Yaw rate sensor, 623
- Yaw roll model, 623
- Yaw rotation, 623
- Yaw-weighted drag coefficient, 623
- Yellow diamond/square, 397
- Yield strength, 624
- Yoke, 624
- Y-pipe, 624
- Y-type alternator stator, 625

Z

- Zener diode, 627
- Zero resistance, 627
- Zeroth law of thermodynamics, 627–628
- Zirconia oxygen sensor, 628

