

Index

a

ALOHA 110
 Ambient energy models
 linear regression 13
 normalized root mean squared error 13
 polynomial regression 13
 prediction error 14
 random forest 13
 support vector machine 13
 wavelets 14
 Amplification factor 224
 Amplify-and-forward 93, 222, 224, 247,
 260, 271, 276, 280
 Asynchronous protocols 101
 Average energy to minimum eigenvalue
 detector 187

b

Back-scatter communications 50
 Battery models 35
 Binary frequency shift keying 48, 56–60
 Binary phase shift keying 48, 56–60

c

Capacity-energy function 128
 Carrier sensing multiple access with
 collision avoidance 103
 Circuit power 88
 Cognitive radio 175
 Collaborative spectrum sensing 178
 Communications models 39
 Conversion efficiency 26
 efficiency-frequency relationship 30
 efficiency-input relationship 29, 84
 Correlation coefficient 139

d

Decode-and-forward 222, 225, 249, 279
 Delay-constrained 227, 229, 248, 249, 253,
 272
 Delay-tolerant 227, 229, 248, 249, 254
 Delay-violation probability 122
 Diode equation 22
 Diode ideality factor 22
 Directed power transfer 151
 Doubly near-far problem 138
 Duty cycling 102
 Dynamic power splitting 134

e

Effective capacity 121
 Electromagnetic energy 9
 ambient 9, 12, 107, 112, 210
 far field 9
 near field 9
 power densities 9, 10, 26
 End-to-end SNR 226, 228
 Energy adaptive media access control
 103
 Energy causality constraint 54, 114, 212,
 238
 Energy detection 177, 182
 Energy harvesting source 260
 Energy matrix 164
 Energy or power outage 103, 150
 Energy sources
 predictive models 10
 types 5
 Energy waveform 84
 linear 85
 non-linear 86

Energy waveform (*contd.*)

optimization 85

Exponentially weighted moving average
10

f

Feature detection 177, 186

5G 3

Fixed-power transmission 42, 43, 55,
189–190

Full relay selection 231

g

Green communications 2

Guard zone 199

h

Harmonic mean 226

Harvest-store-use 55, 189–190

Harvest-use protocol 35, 55, 136, 189–190

Harvest zone 199

Hybrid access point 126, 135, 192, 204,
241

i

Incremental relaying 225

Interference 153–169, 270

Intermittent motion energy 7

Interweave 180

Invariance principle 64

Isotropic power transfer 151

j

Jain's fairness index 106

l

Link layer channel model 121

m

Markov model 33, 200

Matching network 27

Max SNR routing 113

Maximum eigenvalue detector 186

Maximum likelihood estimation 64, 67, 81

Maximum-to-minimum eigenvalue
detector 187

Mean-squared error 74–79

Mechanical energy 5, 6

electromagnetic method 7

electrostatic method 7

piezoelectric method 7

power densities 7, 10

Media access control 101, 102

Models of harvested power 31

cumulative distribution function 34, 42

probability density function 34, 42

time-correlated stochastic models 33

time-uncorrelated stochastic models 33

Moment-based estimation 62–74

Moment-matching 160

Multi-hop 112, 272

n

Network lifetime 101

Neyman–Pearson rule 184

Noise uncertainty 183

Non-orthogonal multiple access 84, 91

o

Opportunistic routing 112

Overlay 181

p

Partial relay selection 231

Peak transmission power limit 194

Peer harvesting 163

Photovoltaic panels 19

efficiency 20, 22

loss 20

maximum power position tracking 22

one-diode model 23

photoconductivity 21

two-diode model 23

Physical layer security 89

Poisson distribution 33, 199

Power beacon 126, 150

Power splitting 130, 132, 171, 215, 248,
250, 263, 273, 280, 282

factor 132

noise 133, 171

power splitter 134–135

Probability of detection 184

Probability of false alarm 184

r

Random vibration energy 6
 Rate-energy function 131, 133, 134, 137, 171
 Rate-energy tradeoff 128, 135
 Receiver operating characteristics 185
 Receiver sensitivity 157, 199
 Rectenna 26
 Rectifier 27
 RF energy harvester 25
 Round-robin 163
 Routing 101

s

Secrecy outage probability 90
 Secrecy rate 90
 Sensing-throughput tradeoff 179
 Signal causality 239
 Signal outage 150, 201
 Simultaneous wireless information and power transfer 126, 127
 Solar/light energy 5, 8
 models 10
 power densities 8, 10, 20
 Spatial spectrum opportunities 176
 Spectrum scarcity 175
 Spectrum sensing 177
 Spectrum under-utilization 175
 Standard testing conditions 24
 current temperature coefficient 23
 maximum power 23
 open-circuit voltage 23

short-circuit current 23
 voltage temperature coefficient 24

Steady flow energy 7
 Supercapacitor leakage 36
 Synchronous protocols 101

t

Temporal spectrum opportunities 176
 Thermal energy 8
 Time division multiple access 110
 Time switching 130, 171, 247, 249, 260, 271, 276
 coefficient 130
 time switcher 134–135
 Transmission probability 43, 200
 Transmission scheduling 118
 2-D linear filter 12
 Two-way relaying 223, 233

u

Underlay 180

v

Variable-gain amplification 224
 Variable-power transmission 42, 47, 55, 189–190

w

Weather conditioned moving average 11
 Wireless charging aware routing 117
 Wireless power 5, 84, 103, 117, 125, 204
 Wireless powered communications 126